

TECHNICAL DATA

	F-TYPE 300PS Coupé	F-TYPE 300PS Convertible
ENGINE & TRANSMISSION		
Engine capacity (cc)	1,997	
Cylinders	Four in-line	
Valves per cylinder	4; DOHC, electrohydraulic fully variable intake valve lift system	
Bore/ stroke (mm)	83.0/ 92.3	
Compression ratio	9.5:1	
Fuel injection	200bar direct injection	
Boosting system	Single twin-scroll turbocharger with ceramic ball bearings	
Power PS (kW)	300 (221) @ 5,500rpm	
Torque Nm (lb ft)	400 @ 1,500-4,500rpm	
Transmission	8-speed Quickshift	
Gear ratios (:1)		
1st	4.714	
2nd	3.143	
3rd	2.106	
4th	1.667	
5th	1.285	
6th	1.000	
7th	0.839	
8th	0.667	
Reverse	3.295	
Final Drive ratio	3.55	
CHASSIS		
Front suspension	Double wishbone	
Rear suspension	Double wishbone	
Front brakes	Single-piston sliding caliper; 355mm ventilated discs	
Rear brakes	Single-piston sliding caliper; 325mm ventilated discs	
Steering	Rack-and-pinion; electromechanical	
DIMENSIONS		
Length (mm)	4,470	4,470
Width inc./ excl. mirrors (mm)	2,042/ 1,923	2,042/ 1,923
Height (mm)	1,311	1,307
Wheelbase (mm)	2,622	2,622
Track front/ rear (mm)	1,596/ 1,647	1,596/ 1,647
Weight; EU Unladen (kg)	1,595	1,615
Weight; DIN (kg)	1,520	1,540
Loadspace volume (litres)	283/ 509 with/ without parcel tray	200
Fuel tank (useable) litres	63	63
PERFORMANCE & FUEL ECONOMY		
0-100km/h (sec)	5.7	5.7
Top speed (km/h)	250	250
Fuel consumption (litres/100km) NEDC equivalent combined	8.1	8.1
CO ₂ emissions (g/km) NEDC equivalent combined	184	184

Manufacturer's figures; correct at time of going to press

TECHNICAL DATA

	F-TYPE 450PS RWD Coupé	F-TYPE 450PS RWD Convertible
ENGINE & TRANSMISSION		
Engine capacity (cc)	5,000	
Cylinders	V8 Supercharged	
Valves per cylinder	4; DOHC	
Bore/ stroke (mm)	92.5/ 93.0	
Compression ratio	9.5:1	
Fuel injection	150bar direct injection	
Power PS (kW)	450 (331) @ 6,000rpm	
Torque Nm (lb ft)	580 @ 2,500-5,000rpm	
Transmission	8-speed Quickshift	
Gear ratios (:1)		
1st	4.714	
2nd	3.143	
3rd	2.106	
4th	1.667	
5th	1.285	
6th	1.000	
7th	0.839	
8th	0.667	
Reverse	3.317	
Final Drive ratio	2.56	
CHASSIS		
Front suspension	Double wishbone	
Rear suspension	Double wishbone	
Front brakes	Twin-piston sliding caliper; 380mm ventilated discs	
Rear brakes	Single-piston sliding caliper; 376mm ventilated discs	
Steering	Rack-and-pinion; electromechanical	
DIMENSIONS		
Length (mm)	4,470	4,470
Width inc./ excl. mirrors (mm)	2,042/ 1,923	2,042/ 1,923
Height (mm)	1,311	1,307
Wheelbase (mm)	2,622	2,622
Track front/ rear (mm)	1,584/ 1,628	1,584/ 1,628
Weight; EU Unladen (kg)	1,735	1,735
Weight; DIN (kg)	1,660	1,660
Loadspace volume (litres)	299/ 509 with/ without parcel tray	233
Fuel tank (useable) litres	70	70
PERFORMANCE & FUEL ECONOMY		
0-100km/h (sec)	4.6	4.6
Top speed (km/h)	285	285
Fuel consumption (litres/100km) NEDC equivalent combined	10.6	10.6
CO ₂ emissions (g/km) NEDC equivalent combined	244	244

Manufacturer's figures; correct at time of going to press

TECHNICAL DATA

	F-TYPE 450PS AWD Coupé	F-TYPE 450PS AWD Convertible
ENGINE & TRANSMISSION		
Engine capacity (cc)	5,000	
Cylinders	V8 Supercharged	
Valves per cylinder	4; DOHC	
Bore/ stroke (mm)	92.5/ 93.0	
Compression ratio	9.5:1	
Fuel injection	150bar direct injection	
Power PS (kW)	450 (331) @ 6,000rpm	
Torque Nm (lb ft)	580 @ 2,500-5,000rpm	
Transmission	8-speed Quickshift	
Gear ratios (:1)		
1st	4.714	
2nd	3.143	
3rd	2.106	
4th	1.667	
5th	1.285	
6th	1.000	
7th	0.839	
8th	0.667	
Reverse	3.317	
Final Drive ratio	2.56	
CHASSIS		
Front suspension	Double wishbone	
Rear suspension	Double wishbone	
Front brakes	Twin-piston sliding caliper; 380mm ventilated discs	
Rear brakes	Single-piston sliding caliper; 376mm ventilated discs	
Steering	Rack-and-pinion; electromechanical	
DIMENSIONS		
Length (mm)	4,470	4,470
Width inc./ excl. mirrors (mm)	2,042/ 1,923	2,042/ 1,923
Height (mm)	1,311	1,307
Wheelbase (mm)	2,622	2,622
Track front/ rear (mm)	1,584/ 1,628	1,584/ 1,628
Weight; EU Unladen (kg)	1,818	1,838
Weight; DIN (kg)	1,743	1,763
Loadspace volume (litres)	299/ 509 with/ without parcel tray	233
Fuel tank (useable) litres	70	70
PERFORMANCE & FUEL ECONOMY		
0-100km/h (sec)	4.6	4.6
Top speed (km/h)	285	285
Fuel consumption (litres/100km) NEDC equivalent combined	11.0	11.0
CO ₂ emissions (g/km) NEDC equivalent combined	252	252

Manufacturer's figures; correct at time of going to press

TECHNICAL DATA

	F-TYPE 575PS AWD Coupé	F-TYPE 575PS AWD Convertible
ENGINE & TRANSMISSION		
Engine capacity (cc)	5,000	
Cylinders	V8 Supercharged	
Valves per cylinder	4; DOHC	
Bore/ stroke (mm)	92.5/ 93.0	
Compression ratio	9.5:1	
Fuel injection	150bar direct injection	
Power PS (kW)	575 (423) @ 6,500rpm	
Torque Nm (lb ft)	700 @ 3,500-5,000rpm	
Transmission	8-speed Quickshift	
Gear ratios (:1)		
1st	4.714	
2nd	3.143	
3rd	2.106	
4th	1.667	
5th	1.285	
6th	1.000	
7th	0.839	
8th	0.667	
Reverse	3.317	
Final Drive ratio	2.56	
CHASSIS		
Front suspension	Double wishbone	
Rear suspension	Double wishbone	
Front brakes	Twin-piston sliding caliper; 380mm ventilated discs	
Rear brakes	Single-piston sliding caliper; 376mm ventilated discs	
Steering	Rack-and-pinion; electromechanical	
DIMENSIONS		
Length (mm)	4,470	4,470
Width inc./ excl. mirrors (mm)	2,042/ 1,923	2,042/ 1,923
Height (mm)	1,311	1,307
Wheelbase (mm)	2,622	2,622
Track front/ rear (mm)	1,584/ 1,610	1,584/ 1,610
Weight; EU Unladen (kg)	1,818	1,838
Weight; DIN (kg)	1,743	1,763
Loadspace volume (litres)	299/ 509 with/ without parcel tray	233
Fuel tank (useable) litres	70	70
PERFORMANCE & FUEL ECONOMY		
0-100km/h (sec)	3.7	3.7
Top speed mph (km/h)	186 (300)	186 (300)
Fuel consumption mpg (litres/100km) NEDC equivalent combined	25.6 (11.0)	25.6 (11.0)
CO ₂ emissions (g/km) NEDC equivalent combined	252	252

Manufacturer's figures; correct at time of going to press